

Model: ST-704

DESCRIPTION:

Wall mount type, designed for indoor installation
 Extruded aluminium body and acrylic as it's diffuser
 Available in various finished: black, white, grey,etc

TECHNICAL CHARACTERISTICS:

IP Protection: IP20/ IP54
 IK Protection: IK08
 Safety Class: Class I
 Voltage/Frequency: 85-265V,50/60 Hz
 Working Temperature: -35°C ~ +65°C

Application

LED SPECIFICATIONS:

LEDS: SMD, 15W
 Color Temperature: 3000K/4000K/6000K
 Lumen: 1200lm

DIMENSION:

Length: 250mm Width: 60mm Height: 100mm

MATERIALS/FINISHES:

Structure Material: Die-casting aluminium Diffuser Material: Acrylic
 Structure Finish: Die-cast Black, White, Grey

SAMPLE FOR STICK LABEL WITH YOUR LOGO:



Product Description	YOUR LOGO		
15W LED WALL LIGHT			
Color Temp	Protection		
3000K	IP65		
Power Supply	Power Rate		
85-265v,50-60Hz	15W		
Product #:xxxxxxx			
Tel:		CLASS I	
Fax:			
Email:	EEC A	IP65	IK 08
website:			
Address:			

15W LED WALL LIGHT	YOUR LOGO	
Product#: xxxxxx		
Power: 15W	Input: 85-265V,50-60Hz	IP65
Stick Lable of Lamp Body		
	≥80	CRI
	2.7	kwh/1000h
	90 degree	Beam Angle
	15W	Max LED Watt
	3000K	Color Temperature
	0%~95%	Environmental Humidity
	1200lm	Luminous Flux
	-35°C ~ +65°C	Environmental Temp

Stick Label of Box & Carton

Energy Consumption Lable