

### Model: ST-713

#### DESCRIPTION:

Wall mount type, designed for indoor installation  
 Extruded aluminium body and glass as it's diffuser  
 Available in various finished: black, white, grey,etc

#### TECHNICAL CHARACTERISTICS:

IP Protection: IP20/ IP54  
 IK Protection: IK08  
 Safety Class: Class I  
 Voltage/Frequency: 85-265V,50/60 Hz  
 Working Temperature: -35°C ~ +65°C

#### LED SPECIFICATIONS:

LEDS: 2+2W  
 Color Temperature: 3000K/4000K/6000K  
 Lumen: 320lm

#### DIMENSION:

Length: 130mm    Width: 80mm    Height: 37mm

#### MATERIALS/FINISHES:

**Structure Material:** Die-casting aluminium      **Diffuser Material:** Glass  
**Structure Finish:** Die-cast Black, White, Grey

#### Application



#### SAMPLE FOR STICK LABELERL WITH YOUR LOGO:

|   |                           |
|---|---------------------------|
| Product Description<br><b>2+2W LED WALL LIGHT</b> | <b>YOUR LOGO</b>          |
| Color Temp<br><b>3000K</b>                        | Protection<br><b>IP65</b> |
| Power Supply<br><b>85-265v,50-60Hz</b>            | Power Rate<br><b>2+2W</b> |
| Product #:xxxxxxx                                 |                           |
| Tel:  |                           |
| Fax:  |                           |
| Email:  |                           |
| website:  |                           |
| Address:  |                           |

Stick Label of Box & Carton

|                                 |                                  |
|---------------------------------|----------------------------------|
| <b>2+2W LED WALL LIGHT</b>      | <b>YOUR LOGO</b>                 |
| Product#: xxxxxx                |                                  |
| Power: 2+2W                     | Input: 85-265V,50-60Hz           |
|                                 | IP65                             |
| <b>Stick Lable of Lamp Body</b> |                                  |
|                                 | ≥80 CRI                          |
|                                 | 2.7 kwh/1000h                    |
|                                 | 90 degree Beam Angle             |
|                                 | 2+2 Max LED Watt                 |
|                                 | 3000K Color Temperature          |
|                                 | 0%~95% Environmental Humidity    |
|                                 | 320lm Luminous Flux              |
|                                 | -35°C ~ +65°C Environmental Temp |

Energy Consumption Lable